

SSSB SERIES



رقم المنتج	رقم السكن	حجم العمود	D	B	C	تصنيفات الحمل الأساسية Cr	تصنيفات التحميل الأساسية Cor	المادة	الدقة	ISO 9001	RoHS	التخفيضات
Sssb207 22	SSSB207-22	1-3/8 in	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Sssb207 20	SSSB207-20	1-1/4 in	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.699 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Sssb206 20	SSSB206-20	1-1/4 in	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Sssb206 19	SSSB206-19	1-3/16 in	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Sssb206	SSSB206	30 mm	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Sssb206 18	SSSB206-18	1-1/8 in	62.0 mm 2.441 in	30.0 mm 1.181 in	16.0 mm 0.630 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Sssb205 16	SSSB205-16	1 in	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb	Stainless Steel	P0	YES	YES	Standard
Sssb205	SSSB205	25 mm	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb	Stainless Steel	P0	YES	YES	Standard
Sssb205 15	SSSB205-15	15/16 in	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb	Stainless Steel	P0	YES	YES	Standard

SSSB SERIES

Sssb205 14	SSSB205-14	7/8 in	52.0 mm 2.047 in	27.0 mm 1.063 in	15.0 mm 0.591 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb	Stainless Steel	P0	YES	YES	Standard
Sssb204	SSSB204	20 mm	47.0 mm 1.850 in	25.0 mm 0.984 in	14.0 mm 0.551 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb	Stainless Steel	P0	YES	YES	Standard
Sssb204 12	SSSB204-12	3/4 in	47.0 mm 1.850 in	25.0 mm 0.984 in	14.0 mm 0.551 in	12.8 kN 28.2 lb	6.65 kN 14.7 lb	Stainless Steel	P0	YES	YES	Standard
Sssb203	SSSB203	17 mm	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb	Stainless Steel	P0	YES	YES	Standard
Sssb202 10	SSSB202-10	5/8 in	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb	Stainless Steel	P0	YES	YES	Standard
Sssb202	SSSB202	15 mm	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb	Stainless Steel	P0	YES	YES	Standard
Sssb201 8	SSSB201-8	1/2 in	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb	Stainless Steel	P0	YES	YES	Standard
Sssb201	SSSB201	12 mm	40.0 mm 1.575 in	22.0 mm 0.866 in	12.0 mm 0.472 in	9.55 kN 21.1 lb	4.80 kN 10.6 lb	Stainless Steel	P0	YES	YES	Standard
Sssb208	SSSB208	40 mm	80.0 mm 3.150 in	34.0 mm 1.339 in	18.0 mm 0.709 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb	Stainless Steel	P0	YES	YES	Standard
Sssb208 24	SSSB208-24	1-1/2 in	80.0 mm 3.150 in	34.0 mm 1.339 in	18.0 mm 0.709 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb	Stainless Steel	P0	YES	YES	Standard
Sssb207 23	SSSB207-23	1-7/16 in	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Sssb207	SSSB207	35 mm	72.0 mm 2.835 in	32.0 mm 1.260 in	17.0 mm 0.669 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard