

SJF-T SERIES



رقم الجزء	d	B	C1	d2	d3 UNF 2B	h1	l1	d4	L11	L2	قطر الكرة مم (بوصة))	المادة	نطاق درجات الحرارة	RoHS	ISO: 9001	التخليص الشعاعي
Sjf 10t	15.875 (0.6250)	19.05 (0.750)	17.27 (0.562)	38.74 (1.525)	38582	63.5 (2.500)	34.93 (1.375)	25.4 (1.000)	22.22 (0.875)	82.87 (3.262)	26.97 (1.062)	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjf 8t	12.7 (0.5000)	15.88 (0.625)	12.7 (0.500)	33.96 (1.337)	36942	53.98 (2.125)	28.58 (1.125)	22.22 (0.875)	19.05 (0.750)	70.96 (2.97)	22.22 (0.875)	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjf 7t	11.112 (0.4375)	14.27 (0.562)	11.1 (0.437)	29.21 (1.150)	7/16-20	46.02 (1.812)	25.4 (1.000)	19.05 (0.750)	15.88 (0.625)	60.60 (2.38)	19.83 (0.781)	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjf 6t	9.525 (0.3750)	12.7 (0.500)	10.31 (0.406)	26.03 (1.025)	37857	41.28 (1.625)	22.22 (0.875)	17.45 (0.687)	14.27 (0.562)	54.29 (2.13)	17.45 (0.687)	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjf 5t	7.938 (0.3125)	11.11 (0.437)	8.74 (0.344)	22.86 (0.900)	5/16-24	34.93 (1.375)	17.45 (0.687)	12.7 (0.500)	11.1 (0.437)	46.35 (1.825)	15.06 (0.593)	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjf 4t	6.35 (0.2500)	9.53 (0.375)	7.14 (0.281)	20.47 (0.806)	37009	33.32 (1.312)	15.88 (0.625)	11.89 (0.468)	9.52 (0.375)	43.55 (1.714)	13.48 (0.531)	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sjf 12t	19.05 (0.7500)	22.23 (0.875)	17.45 (0.687)	45.09 (1.775)	37727	73.03 (2.875)	41.28 (1.625)	28.58 (1.125)	25.4 (1.000)	95.57 (3.762)	31.75 (1.250)	Steel	-20° to 80° C	Compliant	Compliant	Standard