

SPOSB..EC SERIES



رقم الجزء	الوزن (g)	d	فئة Thread S 3A	D1	B	B1	d11	L	l1	L2	RSMIN	قطر الكرة مم (بوصة))	المادة	نطاق درجات الحرارة	RoHS	ISO: 9001	التخليص الشعاعي
Sposb8	122	12.700 (.5000)	-20UNF (.5000)	33.32 (1.312)	12.70 (.500)	15.88 (.625)	17.73 (.698)	78.59 (3.094)	61.93 (2.438)	38.10 (1.500)	0.5 (.020)	23.812 □ 15/16□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb7	77	11.112 (.4375)	-20UNF (.4375)	28.58 (1.125)	11.10 (.437)	14.27 (.562)	14.88 (.586)	68.28 (2.688)	53.98 (2.125)	34.93 (1.375)	0.5 (.020)	20.638 □ 13/16□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb6	54	9.525 (.3750)	-24UNF (.3750)	25.40 (1.000)	10.31 (.406)	12.70 (.500)	13.13 (.517)	61.93 (2.438)	49.23 (1.938)	31.75 (1.250)	0.5 (.020)	18.256 □ 23/32□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb4	23	6.350 (.2500)	-28UNF (.2500)	19.05 (.750)	7.14 (.281)	9.53 (.375)	9.02 (.355)	49.20 (1.937)	39.67 (1.562)	25.40 (1.000)	0.5 (.020)	13.097 □ 33/64□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb5	36	7.938 (.3125)	-24UNF (.3125)	22.23 (.875)	8.74 (.344)	11.10 (.437)	11.35 (.447)	58.72 (2.312)	47.63 (1.875)	31.75 (1.250)	0.5 (.020)	15.875 □ 5/8□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb2 5	9.1	3.967 (.1562)	-32UNC (.1640)	14.27 (.562)	5.56 (.219)	7.14 (.281)	6.32 (.249)	35.71 (1.406)	28.58 (1.125)	15.88 (.625)	0.3 (.012)	9.525 □ 3/8□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb3	14	4.826 (.1900)	-32UNF (.1900)	15.88 (.625)	6.35 (.250)	7.92 (.312)	7.77 (.306)	39.70 (1.563)	31.75 (1.250)	19.05 (.750)	0.3 (.012)	11.112 □ 7/16□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb2	5.4	3.175 (.1250)	-32UNC (.1380)	11.91 (.469)	4.75 (.187)	6.35 (.250)	4.75 (.187)	29.77 (1.172)	23.80 (.937)	12.70 (.500)	0.3 (.012)	7.938 □ 5/16□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb16	1129	25.400 (1.0000)	-12UNF (1.2500)	69.85 (2.750)	25.40 (1.000)	34.93 (1.375)	32.23 (1.269)	139.70 (5.500)	104.78 (4.125)	53.98 (2.125)	0.5 (.020)	47.625 □ 1 7/8□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb12	295	19.050 (.7500)	-16UNF (.7500)	44.45 (1.750)	17.45 (.687)	22.23 (.875)	24.84 (.978)	95.25 (3.750)	73.03 (2.875)	44.45 (1.750)	0.5 (.020)	33.338 □ 1 5/16□	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sposb10	186	15.875 (.6250)	-18UNF (.6250)	38.10 (1.500)	14.27 (.562)	19.05 (.750)	21.31 (.839)	85.73 (3.375)	66.68 (2.625)	41.28 (1.625)	0.5 (.020)	28.575 □ 1 1/8□	Steel	-50° to 120° C	Compliant	Compliant	Standard