

Stainless Miniature Flanged Ball Bearings



رقم الجزء	ID	OD	العرض	فلانج أود	عرض الحافة	نوع الدرع	الحمل الدائمي	الحمل الثابت	السرعة القصى (X1000 دورة في الدقيقة)	مادة الحلقة	نظام القياس	نوع المحمل	نوع كروية المحمل	تصنيف الدقة	التخفيضات	نطاق درجات الحرارة	RoHS	SGS
SMF115	5 mm	11 mm	4 mm	12.6 mm	0.8 mm	Open	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF105zz	5 mm	10 mm	4 mm	11.6 mm	0.8 mm	Shielded	74 lbf	27 lbf	45	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF105 2rs	5 mm	10 mm	4 mm	11.6 mm	0.8 mm	Sealed	74 lbf	27 lbf	45	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF105	5 mm	10 mm	3 mm	11.2 mm	0.6 mm	Open	74 lbf	27 lbf	45	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF695zz	5 mm	13 mm	4 mm	15 mm	1 mm	Shielded	185 lbf	70 lbf	38.7	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF695 2rs	5 mm	13 mm	4 mm	15 mm	1 mm	Sealed	185 lbf	70 lbf	38.7	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF695	5 mm	13 mm	4 mm	15 mm	1 mm	Open	185 lbf	70 lbf	38.7	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF685zz	5 mm	11 mm	5 mm	12.5 mm	1 mm	Shielded	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF685 2rs	5 mm	11 mm	5 mm	12.5 mm	1 mm	Sealed	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF685	5 mm	11 mm	3 mm	12.5 mm	0.8 mm	Open	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF635zz	5 mm	19 mm	6 mm	22 mm	1.5 mm	Shielded	402 lbf	145 lbf	28.8	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF635 2rs	5 mm	19 mm	6 mm	22 mm	1.5 mm	Sealed	402 lbf	145 lbf	28.8	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF635	5 mm	19 mm	6 mm	22 mm	1.5 mm	Open	402 lbf	145 lbf	28.8	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF625zz	5 mm	16 mm	5 mm	18 mm	1 mm	Shielded	297 lbf	109 lbf	32.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF625 2rs	5 mm	16 mm	5 mm	18 mm	1 mm	Sealed	297 lbf	109 lbf	32.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF625	5 mm	16 mm	5 mm	18 mm	1 mm	Open	297 lbf	109 lbf	32.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF605zz	5 mm	14 mm	5 mm	16 mm	1 mm	Shielded	229 lbf	82 lbf	36	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant

Stainless Miniature Flanged Ball Bearings

SF605 2rs	5 mm	14 mm	5 mm	16 mm	1 mm	Sealed	229 lbf	82 lbf	36	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF605	5 mm	14 mm	5 mm	16 mm	1 mm	Open	229 lbf	82 lbf	36	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF84zz	4 mm	8 mm	3 mm	9.2 mm	0.6 mm	Shielded	68 lbf	23 lbf	50.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF84 2rs	4 mm	8 mm	3 mm	9.2 mm	0.6 mm	Sealed	68 lbf	23 lbf	50.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF84	4 mm	8 mm	2 mm	9.2 mm	0.6 mm	Open	68 lbf	23 lbf	50.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF74zz	4 mm	7 mm	2.5 mm	8.2 mm	0.6 mm	Shielded	44 lbf	17 lbf	54	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF74 2rs	4 mm	7 mm	2.5 mm	8.2 mm	0.6 mm	Sealed	44 lbf	17 lbf	54	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF74	4 mm	7 mm	2 mm	8.2 mm	0.6 mm	Open	54 lbf	19 lbf	54	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF104zz	4 mm	10 mm	4 mm	11.6 mm	0.8 mm	Shielded	122 lbf	44 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF104 2rs	4 mm	10 mm	4 mm	11.6 mm	0.8 mm	Sealed	122 lbf	44 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF104	4 mm	10 mm	3 mm	11.2 mm	0.6 mm	Open	122 lbf	44 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF694zz	4 mm	11 mm	4 mm	12.5 mm	1 mm	Shielded	165 lbf	57 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF694 2rs	4 mm	11 mm	4 mm	12.5 mm	1 mm	Sealed	165 lbf	57 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant